

FF50 - Bizflame Work FR Coverall

Collection: Bizflame™ Work

Range: Flame Resistant Multi-Norm

Shell Fabric: Bizflame Work: 99% Cotton, 1% Carbon Fibre, 350g

Outer Carton: 10

Product information

Ideally suited to off shore industries this top of the range coverall comes in inch sizes for the perfect fit. Certified to a multitude of international standards the Aberdeen coverall offers top protection in a range of hazardous environments.

Bizflame™ Work

BizFlame™ Work has been developed and designed using the highly innovative Bizflame™ Work flame resistant fabric with added anti-static properties. Certified to a range of international standards.

Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

EN ISO 11612 (A1+A2, B1, C1, E2, F1)

EN ISO 11611 Class 2 (A1+A2)

EN 1149 -5

EN 61482-2 EN 61482-1-1 (ELIM 8.6 CAL/CM², ATPV 9.8 CAL/CM²)

EN 61482-2 EN 61482-1-2 APC 1

ASTM F1959/F1959M-12 (ATPV=13.6 Cal/CM² (HAF=82%))



Features

- Protection against radiant, convective and contact heat
- Class 2 welding protection
- Two back patch pockets
- Rule pocket
- Stud adjustable cuffs for a secure fit
- Triple-stitched seams for extra durability
- Radio loops for easy clipping of a radio
- Two tier knee pad pockets allowing two positioning options
- Two-way zip for quick and easy access
- 10 pockets for ample storage
- Sew on flame resistant industrial wash tape

FF50 - Bizflame Work FR Coverall

Commodity Code: 6211321000

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland

Cert No: 2777/13136-03/E00-00

Wash Care



Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	DUN14
FF50ORR36	Orange	43.0	28.0	50.0	1.5400	0.0602	5036108258598	15036108747785
FF50ORR38	Orange	43.0	28.0	50.0	1.5400	0.0602	5036108258604	15036108747792
FF50ORR40	Orange	43.0	28.0	50.0	1.5900	0.0602	5036108258611	15036108747808
FF50ORR41	Orange	43.0	28.0	50.0	1.6500	0.0602	5036108275687	15036108765772
FF50ORR42	Orange	43.0	28.0	50.0	1.6200	0.0602	5036108258628	15036108747815
FF50ORR44	Orange	43.0	28.0	50.0	1.6900	0.0602	5036108258635	15036108747822
FF50ORR46	Orange	43.0	28.0	50.0	1.7300	0.0602	5036108258642	15036108747839
FF50ORR47	Orange	43.0	28.0	50.0	1.7400	0.0602	5036108275694	15036108765789
FF50ORR48	Orange	43.0	28.0	50.0	1.7400	0.0602	5036108258659	15036108747846
FF50ORR50	Orange	43.0	28.0	50.0	1.7900	0.0602	5036108258666	15036108747853
FF50ORR52	Orange	43.0	28.0	50.0	1.7900	0.0602	5036108258673	15036108747860
FF50ORR54	Orange	43.0	28.0	50.0	1.8800	0.0602	5036108258680	15036108747877