

P361 - Trifold Valved Dolomite FFP3 Respirator (Pk10)

Collection: Disposable Mask FFP3

Range: Disposable Masks

Materials: Spunblown Polypropylene, Meltblown Polypropylene, Mono PU, Aluminium, Elastic

Outer Carton: 16



Product information

Flexible trifold design adapts to a variety of different face shapes. Soft nose foam for a secure and comfortable fit. Packed inside individual polybags for hygienic storage and is vending machine ready. Dolomite clogging tested.

Disposable Mask FFP3

Disposable mask FFP3 level, protects against solid and liquid particles of high toxicity. Minimal % of filtration 99%. Protects up to 20 times the TLV (Assigned Protection Factor for FFP3 masks) or up to 50 times TLV (Nominal Protection Factor for FFP3 masks). Examples of applications: Sanding of hard wood (beech, oak) / treatment of wood using copper, chrome or arsenic based products / impact stripping of paint / sanding of cement. Exceptional quality and performance are ensured across our range of disposable masks.

Disposable Masks

Our Biztex® brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex® range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination. The complete Biztex® range includes disposable masks and limited-life garments.

Standards

EN 149:2001 +A1:2009 FFP3 (NR D)

Features

- Flexible shape which allows the mask to be folded flat
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Foam padding around the nose bridge for additional comfort
- Individually wrapped inside hygienic polybag
- Dolomite optional clogging test (D) to provide more comfortable breathing and longer lasting filtration performance
- Individually packed for vending machines
- Retail box which aids presentation for retail sales
- CE certified
- CE-CAT III
- New style



PRODUCT SPECIFICATION & TECHNICAL DATA

P361 - Trifold Valved Dolomite FFP3 Respirator (Pk10)

Commodity Code: 6307909311

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)

John M. Keynesplein 9

, The Netherlands

Cert No: 714896

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
P361WHR	White	43.0	37.0	33.0	0.2410	0.0525	5036108434831	15036108921680