

PS41 - Super HV Ear Defenders

Collection: Ear Muffs

Range: Hearing Protection

Materials: HIPS (High Impact Polystyrene), Mesh with PU Foam, Polyoxymethylene, Stainless Steel

Outer Carton: 48

Product information

This hi-visibility colour ear defender folds to palm size preventing external contamination.

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colours for earmuffs allow a personalised choice. An updated range of earplugs complete our competitive and performing offer.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Standards

EN 352-1 (SNR 30dB)

ANSI S3.19 (NRR 25dB)

AS/NZS 1270 (SLC(80) 31dB - Class 5)



Features

- Hi-Visibility colour for visibility in daylight
- Folds to palm size for better carriage and to keep clean
- Lightweight and comfortable
- Adjustable dual pin system provides multiple positioning for better fit
- SNR 30dB attenuation level
- Classic design ear muff
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- CE certified
- CE-CAT III

PS41 - Super HV Ear Defenders

Commodity Code:

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)
 John M. Keynesplein 9
 , The Netherlands
 Cert No: CE 800492

Michael & Associates, Inc. (Notified Body No.:)
 2766 W. College Ave Suite 1
 PA 16801, United States

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
PS41YER	Yellow	60.0	40.0	40.0	0.2440	0.0960	5036108257263	15036108746634

PERFORMANCES - SOUND ATTENUATION - EN 352-1:2002

PW41/PS41		SNR 30.4dB				H: 33.0 M: 27.8 L: 21.3			
A	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B	Mean Attenuation (dB)	17.8	18.0	22.3	27.2	37.4	33.9	37.4	38.4
C	Standard Deviation (dB)	3.5	2.6	2.0	3.1	3.3	2.2	3.5	5.1
D	Assumed Protection (dB)	14.3	15.4	19.3	24.1	34.0	31.7	33.9	33.3

ANSI TESTING: Michael & Associates, Inc 246 Woodland Drive, State College, PA 16803

PW41/PS41		NRR (NOISE REDUCTION RATING) = 25dB								
A	Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Mean Attenuation (dB)	17.6	21.8	30.7	39.7	35.5	37.3	39.1	34.6	35.6
C	Standard Deviation (dB)	3.1	2.6	2.9	3.0	3.1	2.8	2.7	2.7	3.8

PS41YER