

PW42 - Clip-On Ear Defenders

Collection: Ear Muffs

Range: Hearing Protection

Materials: HIPS (High Impact Polystyrene), Stainless Steel, PVC

Outer Carton: 50

Product information

The ear defenders can be put into the stand off position. Compatible with Expertbase helmets. Easy to clip on. Available in colourways red and yellow.

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colours for earmuffs allow a personalised choice. An updated range of earplugs complete our competitive and performing offer.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Standards

EN 352-3 (SNR 25dB)

ANSI S3.19 (NRR 22dB)



Features

- Easy to clip-on
- Compatible with Expertbase Helmets
- SNR 25dB attenuation level
- Adjustable dual pin system provides multiple positioning for better fit
- Ear defenders can be comfortably repositioned when not in use
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- CE certified
- CE-CAT III

PW42 - Clip-On Ear Defenders

Commodity Code: 3926909790

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)
 John M. Keynesplein 9
 , The Netherlands
 Cert No: CE 800492

BSI Assurance UK Ltd (Notified Body No.: AB: 0086)
 The British Standards Institution
 MK5 8PP, United Kingdom
 Michael & Associates, Inc. (Notified Body No.:)
 2766 W. College Ave Suite 1
 PA 16801, United States

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	DUN14
PW42YER	Yellow	58.0	43.0	60.0	0.2640	0.1496	5036108171774	15036108636256

PERFORMANCES - SOUND ATTENUATION - EN 352-3:2002

PW42/PS42									
A	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B	Mean Attenuation (dB)	12.4	14.4	17.9	27.3	34.1	34.8	32.8	32.3
C	Standard Deviation (dB)	5.2	4.9	4.5	4.2	4.2	4.5	4.6	6.4
D	Assumed Protection (dB)	7.2	9.4	13.4	23.1	29.9	30.4	28.2	26.0
SNR 25.9dB H:29.3dB M: 23.8dB L: 15.5dB									

PERFORMANCES - SOUND ATTENUATION - ANSI S.19-1974

PW42/PS42										
A	Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Mean Attenuation (dB)	147.4	20.2	28.0	37.5	34.1	34.6	36.4	35.3	35.0
C	Standard Deviation (dB)	3.1	3.7	3.9	3.8	3.5	3.3	4.0	4.1	4.5
NRR (NOISE REDUCTION RATING) = 22dB										

ANSI TESTING: Michael & Associates, Inc 246 Woodland Drive, State College, PA 16803

PW42YER